



PSE 300 HD

Fully automatic single chamber PowerSpray®-system with 2step process (cleaning / rinsing, drying)

Cleans Screens, stencils, solder carriers, misprints from SMD paste, flux, oil, dust, grease

Capacity: Screens, stencils, frames and carriers up to a size of 780 x 950 mm (31" x 37,5")

Part number: 0905PSE3HD




Certifications:

This water free operating system was certified in its basic version for its energy saving processing and for the standard integration of comprehensive safety features.

- Compact system with two circuits and two tank function
- Waterless / independent, no water / waste water connection necessary
- Comfortable push one button operation
- Fully automatic 2step process: cleaning / rinsing, drying with HotSpeed warm air
- Vertical rotor system with two asynchronous spray rotors for thorough wetting (no blind spots)
- Process and service intervals PLC controlled
- Process sections made of electrolysis and high temperature resistant elements
- Safe installation close to the production line possible; no special protection required
- Extremely compact - maximum capacity on a very small footprint


Key applications




Screens



Stencils



Misprints



Solder carriers

The **kolb** PSE economy line is a quality series of advanced cleaning systems, which focuses on all essential criteria for a qualified cleaning process and therefore stands for attractive purchase prices.

kolb PSE 300 HD is an extremely compact first-rate performance PowerSpray® system designed and manufactured in Germany for smaller quantities with very short cycle times due to an intelligent 2step process with HotSpeed warm air drying.

PSE 300 HD delivers best possible cleaning of screens, stencils, misprints and solder frames, today a prerequisite for reproducible quality in production, the reduction of expensive production stand-stills and as well for high customer satisfaction.

The cleaning system can be operated with all common electronics cleaning supplies (detergents / chemistry, etc.) which are approved by the manufacturer.








PSE 300 HD

Fully automatic single chamber PowerSpray®-system with 2step process (cleaning / rinsing, drying)

Part number: 0905PSE3HD



Application overview

Optional suitable	Most suitable	Optional suitable	Not suitable	Not suitable
				
Assembled PCBs Hybrids Misprints	Stencils Screens, PumpPrints Misprints	Solder frames Solder carriers Solder masks	ESD Boxes Containers Magazines	Condensation traps Filters Steel sheets

Optional suitable applications can also be optimally realized with the appropriate options.

Cleaning / rinsing (key process 1): From the system tank a communicating cleaning and rinsing liquid is sucked by a magnetically coupled pump unit and routed with a controllable volume flow into the ASYNCHRO® spray rotors with patented PUSHFORCE® nozzles. Their geometry ensures a comprehensive and thorough cleaning, even in inaccessible and critical areas. The liquid is continuously filtered in circulation, so that the system progressively enters the rinsing process after removing the contamination.

Drying (key process 2): Drying is carried out by a HotSpeed warm air unit with fan and heating coil in a single air duct. The residual moisture on the product is evaporated at 40 - 45 ° Celsius.

Cycle time: < 30 min., depending on contamination and detergent

Maintenance: The system has a removable panel on the right side. In the maintenance area among others the pump-out set is available. Tank levels as well as pressure values and maintenance cycles are monitored by the PLC. The tank level is also easily controllable through a window in the system front.



PSE 300 HD

Fully automatic single chamber PowerSpray®-system with 2step process (cleaning / rinsing, drying)

Part number: 0905PSE3HD




Main standard features

- PowerSpray® technology bundle: magnetically coupled S-Power pump unit, twofold ASYNCHRO® volume-spray rotorsystem with PUSHFORCE® nozzles, "Option100" softwareprogram (100 freely selectable programs)
- Magnetic coupled pump unit
- Siemens LOGO Programmable Logic Controller (PLC)
- Full flow coarse filter (process chamber)
- HotSpeed warm air drying
- ClosedLoop reprocessing of cleaning and rinsing fluid
- Safety features: safety interlock on the process chamber door, overflow alarm for all tank sections, overheating protection for all heating and drying elements, end switches for all motor-driven valves and drives, personnel protection insulation
- Front cover made of stainless steel, side and rear covers in painted steel
- Process sections made of electrolysis resistant elements

Main options

- Cascaded filter system
- Drip & storage reservoir
- Exhaust control
- Full stainless steel housing
- Sediment filter for cleaning / rinsing tank



PSE 300 HD

Fully automatic single chamber PowerSpray®-system with 2step process (cleaning / rinsing, drying)

Part number: 0905PSE3HD



Technical data

Technology base	kolb PowerSpray®
Capacity	Screens, stencils, frames, carriers up to 80 x 950 mm (31" x 37,5")
Process chamber dimensions	W 350 • D 980 • H 920 mm
Volume tank	ca. 75 - 100 l
Power supply	400 V AC, 16 A CEE / 3PH / 50 or 60 HZ
Power consumption	ca. 2.2 kW
Control system	PLC (Siemens LOGO)
Temperature load	up to 55 °C
Filter system	up to three stage - 1. Full flow coarse filter < 2 mm, 2. Sediment filter inside the tank, 3. 20" fine filter (1 - 100 µm - process dependent)
Exhaust connection	Ø 160 mm, exhaust capacity 200 to 300 m ³ / h
Footprint	800 x 1.200 mm
Operating condition room temperature	20 - 35 °C
Operating noise	63 dB (A)
Empty weight	330 kg

